

METRO series



Description

- Screw coupling multi contact range watertight, ruggedised for multipurpose application, light alloy and brass shell.

Application

- Rolling Stock Equipments (Intercoach and Undercoach Applications)

Technical features

Mechanical

- Shells:
 - plug: aluminium with brass nickel plated locking screw
 - backshell: cable clamp for rigid cables
 - receptacle: brass nickel plated
 - polarization: 5 keys



- Layouts: 1 to 48 cts (power and signals contact)
- Insulator: Neoprene + Noryl
- Contact type: crimp and solder
Material brass with nickel + gold plating

- Design: cone-shaped mating
- Endurance: 500 cycles
- Protection index: IP68 (5 bars)
- Working temperature: -30°C +120°C

METRO series



Contact Layouts



<p>BIS # 261127-20MT</p> <p>27 contacts \varnothing 2 dismontary / rear</p>	<p>BIS # 261142-20MT</p> <p>42 contacts \varnothing 2 dismontary / rear</p>	<p>BIS # 261127-20</p> <p>27 contacts \varnothing 2</p>	<p>BIS # 261101-36+46-20</p> <p>1 contact \varnothing 3.6 + 46 contacts \varnothing 2</p>
<p>BIS # 261148-16LT</p> <p>48 contacts \varnothing 1,6</p>	<p>BIS # 261103-70+02-20</p> <p>3 contacts \varnothing 7 + 2 contacts \varnothing 2</p>	<p>BIS # 261107-50</p> <p>7 contacts \varnothing 5</p>	<p>BIS # 261105-50+02-60</p> <p>5 contacts \varnothing 5 2 contacts \varnothing 6</p>
<p>BIS # 261105-70</p> <p>5 contacts \varnothing 7</p>	<p>BIS # 261102-70+01-40+01-30</p> <p>2 contacts \varnothing 7 + 1 contact \varnothing 4 + 1 contact \varnothing 3</p>		

Création et Impression HELIOSERVICE 01 64 70 50 20